COMPLEMENTARY SYSTEMS

KEYBOARD-VIDEO-MOUSE SOLUTIONS (KVM/LCD)

KVM CONSOLES



KVM is a solution for secure access in server farms where simple, universal access is required.



K-SA-171

_ ~ ~ ~ ~ ~ ~ ~ E K-SA-171-S1601P-E K-SA-171-C1601P-E **"**------K-SA-171-S801P-E K-SA-171-C3201P-E

DESCRIPTION:

• Designed for deployment in server rooms or data centers, allowing either direct or remote access to individual servers (or their cascades). Console enables server configuration and administration from all main manufacturers (IBM, HP, DELL, SUN and others). Integrated KVM switch, LCD console (including

keyboard and touch-pad) housed within a compact (1U high) design.


- Available in two types:
 - Sxxxx DB15 direct cable
 - Cxxxx Cat. 5 dongle via twisted pair cable

KVM SETS – LCD DRAWER & KVM SWITCH										
Code ³	Number and type of port	Access via IP	Description							
K-SA-171-S801P-E	8× USB/PS21	-	up to 128 servers by 8-level cascade							
K-SA-171-S1601P-E	16× USB/PS21	-	up to 128 servers by 8-level cascade							
K-SA-171-C1601P-E	16× Cat 5 ²	-	up to 256 servers by 8-level cascade							
K-SA-171-C3201P-E	32× Cat 5 ²	-	up to 256 servers by 8-level cascade							
K-SA-171-CIP3201P-E	32× Cat 5 ²	yes	up to 256 servers by 8-level cascade							

¹ Includes 8 KVM cables (additional cables to be ordered separately)

LCD HOLDERS

K-SA-171-CIP3201P-E



DESCRIPTION:

- PS/2 or USB input into the LCD holder (according to the cabling terminal type)
- · All LCD drawers include a standard English keyboard; other layouts available on request
- Optional language setting (USA, GBR, JPN, DEU, FRA, ITA, RUS, ESP, CHN, KOR, DNK, CHE, NOR and European localization)
- Equipped with a touchpad (with trackball option)
- Multilingual "on-screen" menu
- · Sliding bars with fixed position to prevent movement during typing
- Easy connection to KVM console
- Standard power supply 230 V; 12, 24 and 48 V options available

LCD DRAWERS ONLY											
Code	H (in U)	LCD size	Dimensions (mm)		Dimensions including packing (mm)		Weight (kg)				
			W	D	н	W	D	н	Nett	Gross	
K-SA-171	1	17"	442	650	44	589	856	168	16	22	
K-SA-191	1	19"	442	650	44	589	856	168	17	23	
K-LKD-171	1	17"	442	650	44	589	856	168	15	21	

LCD holders can be combined with individual KVM consoles from the Conteg portfolio. Please don't hesitate to contact us if unable to locate the LCD holder or KVM console you desire. Special consoles and holders not included in standard offer.

² USB, PS/2 dongles or Cat. 5 cords required for use (to be ordered separately)

³ KVM set contains LCD type K-SA-171; can be replaced with any other LCD solution from LCD DRAWERS ONLY table



CONTEG, spol. s r.o. Headquarters:

Na Vitezne plani 1719/4 140 00 Prague 4 Czech Republic Tel.: +420 261 219 182 conteg@conteg.com www.conteg.com

Production plant:

K Silu 2179 393 01 Pelhrimov Czech Republic Tel.: +420 565 300 300

Local Branches/Offices:

Austria/Germany/Switzerland: +420 261 219 182 Benelux: +3176 5420 709 Southeastern Europe: +49 172 8484 346 Finland: +358 50 414 1257 France/Italy/Maghreb: +33160045590 Middle East: +971 55 508 3241 Russia/CIS: +7 495 967 3840 Saudi Arabia: +966 54 000 2341

